

COMPARISON TABLE

DETAILS*	TM001 STD	TM001 HP	TM001 C	TM001 BASIC	TM006	TM006 CLICK	TM006 BASIC
Flow rate (Free flow) at 3 bar	23 l/min	23 l/min	26 l/min	22 l/min	21 l/min	21 l/min	20 l/min
Flow rate (RhC) at 3bar	22 l/min	22 l/min	22 l/min	21.5 l/min	18 l/min	18 l/min	17.5 l/min
Flow rate (RhA) at 3bar	12.5 l/min	12.5 l/min	12.5 l/min	12.5 l/min	12.5 l/min	12.5 l/min	12 l/min
Burst pressure	>25 bar	>35 bar	>35 bar	>25 bar	>35 bar	>35 bar	>25 bar
Durability	100.000 cycles	100.000 cycles	100.000 cycles	50.000 cycles	100.000 cycles	100.000 cycles	50.000 cycles
STANDARD**	TM001 STD	TM001 HP	TM001 C	TM001 BASIC	TM006	TM006 CLICK	TM006 BASIC
EN-1111	•	•	•	•	•	•	•
ASSE 1016	-	•	•	-	•	•	-
GB QB/T2806	•	•	•	•	•	•	•
SANITARY CERTIFICATION**	TM001 STD	TM001 HP	TM001 C	TM001 BASIC	TM006	TM006 CLICK	TM006 BASIC
ACS	•	•	•	•	•	•	•
WRAS	•	•	•	-	•	•	-
KTW (4MS)	•	•	•	-	•	•	-
NSF	•	•	•	-	•	•	-

* Tested at Sedal's lab with Sedal's standard faucet

** Different references. The compliance of standards does not only depend on the thermostatic cartridge but also on the construction of the faucet body and other elements.



Get access to the complete and latest product technical data!



THERMOSTATIC CARTRIDGES

Sedal's Thermostatic Cartridges are high performance valves thanks to the combination of materials, design and quality sensors, providing fast response, high reliability and anti-scalding safety features.



TM001

ACS, WRAS,
4MS, KTW, NSF
CERTIFIED



STANDARD

Standard thermostatic cartridges complying with EN-1111 specifications for shower and bath appliances. With a life cycle of 50,000 cycles, it suits all the design and quality requirements of the market, providing high reliability and high response, with specific anti-scalding safety measures.

✓ ITEMS: TM001, TM001-4MS

BASIC

Basic thermostatic cartridge, combining entry-level product with high-reliability.

✓ ITEM: TM001 BASIC



ACS
CERTIFIED

ACS, WRAS,
4MS, KTW, NSF
CERTIFIED



COMPACT

Its reduced length makes it perfect to fit wall-mounted installations, without giving up any of the standard high-performance features and certifications.

✓ ITEM: TM001 C

HIGH PRESSURE

Thermostatic cartridge specially designed for burst pressure withstand minimum 35 bar. This cartridge is EN-1111 standard compliant.

✓ ITEMS: TM001 HP, TM001 HP NSF, TM001 HP 4MS



ACS, WRAS,
4MS, KTW, NSF
CERTIFIED

TM006

ACS, WRAS,
4MS, KTW, NSF
CERTIFIED



STANDARD

Standard thermostatic cartridges with smaller diameter for compact shower bodies, complying with EN-1111 specifications. With a life cycle of 50,000 cycles, it suits all the design and quality requirements of the market, providing high reliability and high response, with specific anti-scalding safety measures.

✓ ITEMS: TM006, TM006-4MS, TM006-NSF

BASIC

Smaller basic thermostatic cartridge, combining entry-level product with high-reliability.

✓ ITEM: TM006 BASIC



ACS
CERTIFIED

ACS, WRAS,
4MS, KTW, NSF
CERTIFIED



CLICK

Thermostatic cartridge with an axial click system, which allows high precision movement of the handle. This cartridge has been designed according to EN-1111 standards.

✓ ITEM: TM006 CLICK