



Villeroy & Boch

1748

# VICONNECT

The clever connection



# THE CLEVER CONNECTION BEHIND THE WALL

ViConnect always provides the right solution behind the wall – for toilets, bidets, urinals and washbasins. The range includes 13 installation systems, which guarantee a reliable installation for all standard installation situations. Especially the WC-elements for wall-mounted and floor-standing back to wall toilets enable with 5 dry-wall and 4 brick-wall construction elements multiple installation solutions



### Washbasin element:

- Even large washbasins can be installed securely
- The water connections can be freely positioned
- The trap cover can also be installed with SmartFix
- Suitable for concealed siphons



### Toilet elements:

- For all Standard, Compact, XL, Vita and floor-standing toilets
- Perfect for DirectFlush toilets and SupraFix 3.0 attachment
- Simple installation of ViClean shower toilets



### Urinal element:

- Connections can be freely adjusted
- Continuously adjustable flushing time
- Compatible with ViChange
- Also available for ProDetect urinals



### Bidet elements:

- The additional strut provides perfect support for wall-mounted bidets
- The water connections can be freely positioned
- Suitable for all bidet taps



## VICONNECT – PROVEN VILLEROY & BOCH QUALITY

- All products made in Germany.
- Our reliable installation systems are subjected to regular testing in internal trials with both established and new products from Villeroy & Boch.
- The high standard of the Villeroy & Boch installation systems is confirmed by various certificates and endorsements from independent institutes.



## THERE IS A 25-YEAR AVAILABILITY GUARANTEE FOR REPLACEMENT PARTS FOR VICONNECT

# VICONNECT SPORTS IMPRESSIVE TECHNICAL ADVANTAGES



- Intuitive and fast installation of the flush plate thanks to innovative cable technology with bayonet joint



- For M300 and E300 flush plates:
- Intuitive mounting using a magnet technique
  - Surface-mounted as well as flush-mounted
  - Flush-mounted with 1 mm or 5 mm stainless steel frame



## VICONNECT PROMOTES SUSTAINABILITY

- All toilet flush plates with 2-volume flush for reduced water consumption
- Flushing volume is easily adjustable (3/4.5l or 3/6l)



- Flexible wall installation allows a wide range of applications (e.g. corner installation)



SupraFix 3.0  
Villeroy & Boch

- Integrated vertical struts for safe installation with SupraFix 3.0 and WCs with shortened rear panel
- The waste bend is fully depth-adjustable




- Height-adjustable, self-locking feet and adjustable base plates



- The flush flow can be readjusted directly via the inspection opening



- Reduced noise flow thanks to tested filling valve and drain fitting



- Durable frame made from powder-coated steel



ViClean  
Villeroy & Boch

- Ideal for combination with ViClean shower toilets

# EXCLUSIVE DESIGN HIGHLIGHTS FOR INDIVIDUAL BATHROOM DESIGN

The modern flush plates blend perfectly with all bathroom ceramics and furniture fronts from Villeroy & Boch thanks to the different materials and colours. Their timeless design provides plenty of freedom to create individual bathrooms.

## M300

The M300 flush plate boasts a purist design, with elegant glass surfaces adding an exclusive touch to any bathroom.

COLOUR VARIATIONS (FLUSH PLATE/PUSH BUTTONS)



Art.-Nr.: 922160-xx  
Material: Glass



RB Glass Glossy Black /  
Stainless Steel



RA Glass Glossy Grey /  
Stainless Steel




RE Glass Glossy White /  
Stainless Steel

## E300

The E300 comes with 7 different colour combinations, providing the right design for various preferences and requirements.

COLOUR VARIATIONS (FLUSH PLATE/PUSH BUTTONS)



Art.-Nr.: 9221xx-xx  
Material: Plastics



69-AN Black Matt /  
Chrome Matt



69-D8 Anthracite Matt /  
Chrome Matt



69-N5 White Matt /  
Chrome Matt



61-68 White /  
Chrome



80-68 White /  
White



80-61 Chrome /  
Chrome



80-68 Chrome Matt /  
Chrome Matt

### INSTALLATION OPTIONS FOR THE M300/E300

The stainless steel installation set allows the flush plates in the M300 and E300 series to be surface-mounted as well as flush-mounted.



Surface-mounted  
(no additional parts required)



Flush-mounted with a stainless steel frame  
(1 mm) 922159LC installation set flush-mounted



If required: 922158LC distance frame (5 mm)  
for covering uneven tile joints

## L200



Art.-Nr.: 921843-RB  
Material: Glass & LED

Lighting centrepiece for the bathroom. The flush plate has been finished with an illuminated border, turning it into a true centrepiece in the bathroom. The subtle LED light creates a pleasant atmosphere and functions as a nightlight.

Available in Glass Glossy Black

## M200



Art.-Nr.: 922400-xx  
Material: Glass

The glass surface of the M200 flush plate makes the toilet area look extremely elegant.

COLOUR VARIATIONS



RB Glass Glossy Black



RA Glass Glossy Grey



RE Glass Glossy White

## E200



Art.-Nr.: 922490-xx  
Material: Plastics

The modern E200 flush plate features sleek lines and a timeless design.

COLOUR VARIATIONS



61 Chrome



69 Chrome Matt



68 White

## E100



Art.-Nr.: 922485-xx  
Material: Plastics/Stainless Steel

The E100 model has an impressively large round push surface and a very simple operation.

COLOUR VARIATIONS



61 Chrome



69 Chrome Matt



68 White



LC Stainless Steel

## U100



Art.-Nr.: 921944-xx  
Material: Plastics

The 3 urinal flush plates blend perfectly with any bathroom style thanks to their sleek design and when combined with the toilet flush plate they give the bathroom a very attractive overall impression.

COLOUR VARIATIONS



61 Chrome



69 Chrome Matt



68 White

# VICONNECT DRY-WALL CONSTRUCTION ELEMENTS

## WC-ELEMENT FOR DRY-WALL CONSTRUCTION – STANDARD HEIGHT

**Depth 135–205 mm.** For all wall-mounted WCs (Standard, Compact, Vita, XL), for use with SupraFix 3.0, DirectFlush, ViClean\*



MEASUREMENTS (HxWxD):	1120x525x135–205 mm
WEIGHT:	14 kg
ADJUSTMENT RANGE OF FEET:	From unfinished floor level to upper edge of finished floor: 0–200 mm
FASTENING POINTS:	4
OPERATION:	front operated
FLUSH QUANTITY:	3/6l adjustable to 3/4.5l, max. flush quantity 7.5l
CERTIFICATIONS:	EN 14055, WRAS

Art.-Nr. 92246100

## WC-ELEMENT FOR DRY-WALL CONSTRUCTION – LOW

**Depth 155–205 mm.** For all wall-mounted WCs (Standard, Compact, Vita, XL), for use with SupraFix 3.0, DirectFlush



MEASUREMENTS (HxWxD):	820x525x155–205 mm
WEIGHT:	10.8 kg
ADJUSTMENT RANGE OF FEET:	From unfinished floor level to upper edge of finished floor: 0–200 mm
FASTENING POINTS:	4
OPERATION:	front/top operated
FLUSH QUANTITY:	3/6l adjustable to 3/4.5l, max. flush quantity 7.5l
CERTIFICATIONS:	EN 14055, WRAS

Art.-Nr. 92247500

## WC-ELEMENT FOR DRY-WALL CONSTRUCTION – LOW

**Depth 155–205 mm.** For all wall-mounted WCs (Standard, Compact, Vita, XL), for use with SupraFix 3.0, DirectFlush



MEASUREMENTS (HxWxD):	985x525x155–205 mm
WEIGHT:	12.7 kg
ADJUSTMENT RANGE OF FEET:	From unfinished floor level to upper edge of finished floor: 0–200 mm
FASTENING POINTS:	4
OPERATION:	front/top operated
FLUSH QUANTITY:	3/6l adjustable to 3/4.5l, max. flush quantity 7.5l
CERTIFICATIONS:	EN 14055, WRAS

Art.-Nr. 92247800

## WC-ELEMENT FOR DRY-WALL CONSTRUCTION – COMPACT

**Depth min. 90 mm.** For all wall-mounted WCs (Standard, Compact, Vita, XL), for use with SupraFix 3.0, DirectFlush



MEASUREMENTS (HxWxD):	1185x665x min. 90 mm
WEIGHT:	14.8 kg
ADJUSTMENT RANGE OF FEET:	From unfinished floor level to upper edge of finished floor: 0–200 mm
FASTENING POINTS:	6
OPERATION:	front operated
FLUSH QUANTITY:	3/6l adjustable to 3/4.5l, max. flush quantity 7.5l
CERTIFICATIONS:	EN 14055, WRAS

Art.-Nr. 92247600

# VICONNECT FIXING ELEMENTS FOR HANDLES

## WC-SYSTEM FOR DRY-WALL CONSTRUCTION

**Depth 55 mm.** For assembly to left of WC element 9224 61, 9224 65 and for barrier-free installation of a folding support



MEASUREMENTS (HxWxD):	1150x310x55 mm
WEIGHT:	5.35 kg

Art.-Nr. 92198300

## WC-SYSTEM FOR DRY-WALL CONSTRUCTION

**Depth 55 mm.** For assembly to right of WC element 9224 61, 9224 65 and for barrier-free installation of a folding support



MEASUREMENTS (HxWxD):	1150x310x55 mm
WEIGHT:	5.35 kg

Art.-Nr. 92210900

\*Equipped with an empty conduit for the water pipe for ViClean shower toilets

# VICONNECT DRY-WALL CONSTRUCTION ELEMENTS

## WASHBASIN ELEMENT FOR DRY-WALL CONSTRUCTION

**Depth 135–205 mm.** Individually adjustable for washbasins and hand-rinse washbasins



MEASUREMENTS (HxWxD):	1120x525x75 mm
WEIGHT:	8 kg
ADJUSTMENT RANGE OF FEET:	From unfinished floor level to upper edge of finished floor: 0–200 mm
FASTENING POINTS:	4
DRINKING WATER CONNECTION:	With plywood panel and scaling for free positioning of drinking water pipe wall plates

Art.-Nr. 92214900

## BIDET ELEMENT FOR DRY-WALL CONSTRUCTION

**Depth 135–205 mm.** Individually adjustable for bidets



MEASUREMENTS (HxWxD):	1120x525x100 mm
WEIGHT:	10,5 kg
ADJUSTMENT RANGE OF FEET:	From unfinished floor level to upper edge of finished floor: 0–200 mm
FASTENING POINTS:	4
DRINKING WATER CONNECTION:	With plywood panel and scaling for free positioning of drinking water pipe wall plates

Art.-Nr. 92214800

## URINAL ELEMENT FOR DRY-WALL CONSTRUCTION

**Depth 135–205 mm.** Compatible with all Villeroy & Boch urinals thanks to adjustable struts and universal cartridge valve technology



MEASUREMENTS (HxWxD):	1120x525x98 mm
WEIGHT:	8 kg
ADJUSTMENT RANGE OF FEET:	From unfinished floor level to upper edge of finished floor: 0–200 mm
FASTENING POINTS:	4
OPERATION:	front operated
FLUSH QUANTITY:	Continuously adjustable flow pressure from 4 s–20 s

Art.-Nr. 92198900

## URINAL ELEMENT FOR DRY-WALL CONSTRUCTION

**Depth 135–205 mm.** Compatible with the Villeroy & Boch ProDetect radar control for urinals



MEASUREMENTS (HxWxD):	1120x525x80 mm
WEIGHT:	7 kg
ADJUSTMENT RANGE OF FEET:	From unfinished floor level to upper edge of finished floor: 0–200 mm
FASTENING POINTS:	4
OPERATION:	Electronic urinal flushing control ProDetect

Art.-Nr. 92218500

# VICONNECT CONCEALED CISTERNS

## CONCEALED CISTERN

**Depth 124 mm.** For all wall-mounted WCs (Standard, Compact, Vita, XL) and for floor-standing WCs, back to wall, for use with SupraFix 2.0, DirectFlush



MEASUREMENTS (HxWxD):	735x528x124 mm
WEIGHT:	3.41 kg
FASTENING POINTS:	2
OPERATION:	front operated
FLUSH QUANTITY:	3/6l adjustable to 3/4.5l, max. flush quantity 7.5l
CERTIFICATIONS:	EN 14055, WRAS

Art.-Nr. 92248300

## CONCEALED CISTERN – COMPACT

**Depth 80 mm.** For all wall-mounted WCs (Standard, Compact, Vita, XL) and for floor-standing WCs, back to wall, for use with SupraFix 2.0, DirectFlush



MEASUREMENTS (HxWxD):	740–825x648x80 mm
WEIGHT:	4 kg
FASTENING POINTS:	4
OPERATION:	front operated
FLUSH QUANTITY:	3/6l adjustable to 3/4.5l, max. flush quantity 7.5l
CERTIFICATIONS:	EN 14055

Art.-Nr. 92248200

## CONCEALED CISTERN

**Depth 150 mm.** For all wall-mounted WCs (Standard, Compact, Vita) and for floor-standing WCs, back to wall for use with SupraFix 2.0, DirectFlush



MEASUREMENTS (HxWxD):	820x528x150 mm
WEIGHT:	3.5 kg
FASTENING POINTS:	2
OPERATION:	front / top operated
FLUSH QUANTITY:	3/6l adjustable to 3/4.5l, max. flush quantity 7.5l
CERTIFICATIONS:	EN 14055, WRAS

Art.-Nr. 92237300

# VILLEROY & BOCH

## UNITED KINGDOM

*Villeroy & Boch (UK) Limited  
Bathroom, Wellness and Tiles Division  
267 Merton Road  
London SW 18 5JS*

[www.parsital.com](http://www.parsital.com)

Your sales consultant:

